

SONANCE MOVE EVERYTHING OUTDOORS



As we begin to restructure our new way of life and how our businesses operate, the concept of moving everything outdoors has quickly become the new normal. From classrooms in semi-permanent tents, to sidewalk cafes and open-air worship services, Sonance Outdoor Audio systems help you create peerless outdoor experiences that turn any setting into something memorable.

[#MoveEverythingOutdoors](#)

SONANCE OUTDOOR AUDIO



OMNI-6T

- Four x 1.25" (32mm) Wide-Band Drivers for best-in-class midrange and treble
- 6.5" (165mm) High Excursion Woofer delivers exceptional bass response
- Textured brown enclosure designed to blend into ground cover, garden beds and foliage
- Sonance Laminated Core Transformer for full-fidelity performance in 70V/100V
- Buriable design can be buried up to 8" (203mm) deep, leaving only 6" (152mm) visible above-ground
- Conforms to IP-66 waterproof rating and Mil Spec 810 for humidity, salt spray, UV and temperature



LANDSCAPE SERIES

- Sonance Laminated Core Transformer for full-fidelity performance in 70V/100V
- Adjustable tap settings and 8 Ohm bypass
- Conforms to IP-66 waterproof rating and Mil Spec 810 for humidity, salt spray, UV and temperature
- Triple-sealed enclosures waterproof connectors and marine-grade components
- Satellite Speaker with 1" tweeter and either 4.5" or 6.5" mid-low driver
- Subwoofers with 12" (hardscape or buriable) or 15" (buriable) driver



VP EXTREME

- Adjustable tap settings and 8 Ohm bypass
- Triple-sealed enclosures waterproof connectors and marine-grade components
- Satellite Speaker with 1" tweeter and either 4.5" or 6.5" mid-low driver
- Subwoofers with 12" (hardscape or buriable) or 15" (buriable) driver
- Add Sonance's Laminated Core Transformer for full-fidelity performance in 70V/100V
- Conforms to IP-66 waterproof rating and Mil Spec 810 for humidity, salt spray, UV and temperature



SURFACE MOUNT

- Available in 4", 5.25", 6.5", 8" 2-Way Speakers and an 8" Woofer
- Available in black or white
- Paintable shell and grille
- FastMount bracket for easier installation
- Front-mounted voltage selector tap for easier adjustment
- Front-mounted connector for faster wiring
- Front cover to shield connector and tap selector from the elements
- IPX4, MIL SPEC 810, UV IEC 529 weather and temperature resistant
- UL 1480 and UL 2239 for use in commercial applications