



DS65MU01

65" 4K Commercial LCD Display

Technical Specifications					
Model		DS65MU01			
Item		Specification			
		Analog	Digital		
LCD Module	Resolution	3840 x 2160			
	Color	10 bit 1.07 billion			
	Brightness	350 nits (typ)			
	Contrast Ratio	4000:1 (typ)			
	Viewing Angle	178 degrees			
Backlight Unit		D-LED type			
Viewable Size		1428.48(H) x 803.52(V) mm			
Power Management		Yes / VESA DPMS			
Plug and Play		Yes / VESA DDC2B, DDCCI			
Auto Adjustment		Yes (Contrast / Position / Phase/ Clock)			
Controllable Function		Brightness / Contrast / Color control, etc.			
Input Signal	PC	Video	Analog RGB: 0.7V p-p / 75 ohm terminated	TMD5	
		Sync	Separate: TTL level (Posi / Nega) (with 2.2k ohm terminated)		
		Connector	D-sub x1	DP x1	
	VIDEO	Connector		HDMI x4(with HDCP)	
		SIGNAL LEVEL	0.5Vrms		
	AUDIO	Connector	Phone Jack x 1		
		Control	RS232	2.5mmjack x 1	
			IR	3.5mm Jack x 1	
	Output Signal	AUDIO	RCA L/R x 1, 0.5Vrms with 10k ohm terminated		
Control		RS232	2.5mmjack x 1		
		IR	3.5mm Jack x 1		
Internal Speaker		10W + 10W			
OPS Slot		x1			
IR pass through		Yes			
USB Multi Media Function		Yes			
Smart Insert		No			
Power Supply		Universal (AC 100 - 240V)			
Current Rating		2.5 A @ 100 - 240V,50-60Hz			
Power Consumption		320W (max)			
		170 (Typ)			
		<0.5W (standby mode)			
Operational Environment	Temperature	0- 40degC (Landscape)			
	Humidity	20 - 80% (without condensation)			
Storage Environment	Temperature	-20 - 60degC			
	Humidity	10 - 90% (without condensation)			
Dimension	Net without stand	1458.7 x 834.7 x 81.6 mm			
	Gross	TBA			
Weight	Net without stand	24.8 Kg			
	Gross	39.3 Kg			
Kensington compatible Security Lock		Yes			
Tilt/Swivel/Rotation		Landscape			
Recommended Usage		Up to 16 hours per day			
Complied Regulatory		CB, RCM			
Mounting		VESA: 400mm x 200mm			
Accessories		Power cable, RS232 cable, RS232 Daisy chain cable, HDMI cable, User manual, Warranty card, Remote controller, Batteries			
Warranty		3 year *On-Site (conditions apply) *Refer to warranty terms & conditions			