

UHZ50+

Smart 4K UHD laser home Cinema projector









- True 4K UHD resolution and laser technology HDR and HLG compatible
- Bright 3,000 lumens and stable output, achieves 2,700,000 : 1 Contrast.
- Superb Gaming Experience with 240Hz refresh rate and extremely low 4ms Input Lag for PC gaming
- PureMotion MEMC delivers judder free motion video

Entering the new generation of home entertainment with UHZ50+. With DuraCore Laser technology, UHZ50+ is able to deliver longer-lasting and excellent performance at true 4K UHD resolution with high brightness at 3,000 lumens and 2,700,000:1 contrast. UHZ50+ also comes with the upgraded Smart Home features including Optoma Marketplace, File Manager, Creative Cast, and connectivity with voice assistants, offering the comprehensive home entertainment experience.

With the ability to implement 4-corner adjustment, 2D keystone correction, vertical lens shift, powered 1.3x zoom, and warping at 3*3 matrix, UHZ50+ is also perfectly easy to install in any room at home, or to create a simulation scenario.

Specifications

Specifications	
Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	3,000 lumens
Contrast ratio	2,700,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction -	+/-30°
horizontal	
Keystone correction - vertical	+/-30°
Has vertical auto keystone	Yes
correction	
Displayable colours (millions)	1073.4
Horizontal scan rate	31~135Khz
Vertical scan rate	24 ~ 120HzHz
Uniformity	80%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
Lamp info	, , ,
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance	1.2m - 8.1m
Zoom	1.3
Zoom type	Manual
Focal length	12.81mm~16.74mm
Lens shift	Vertical +10%
Native offset	105%
Lens shift	Yes - {{downloads_link}}
Connectivity	res - {{downloads_iii.ik}}
Connections	Investe 0LIDMI.0.0.0LICD A. 1LIDMI.0.0.(-ADO). 1
Comicolons	Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC), 1 x 12V trigger
	Outputs 1 x Audio 3.5mm, 1 x S/PDIF
	Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync
Wireless - technology	IEEE 802.11 a/b/g/n/ac
Wireless - operating frequency	2.4GHz/5GHz
General	26dB
Noise level (typical)	
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz) HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequentia(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz).
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x788@120Hz, 1280x800@120Hz, 1920x1080@120Hz). HDMI3: Frame Packing(1280x720@50Hz/60Hz,
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) HDM1/ HDM12: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz). HDM13: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz,
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz). HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz),
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1924x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz). HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz, 1920x1080@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz,
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@13.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), 1920x1080@23.98/24Hz), Side by
PC compatibility 2D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1924x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz). HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz, 1920x1080@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz,
PC compatibility 2D compatibility 3D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@3.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), 1320x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz).
PC compatibility 2D compatibility 3D compatibility 3D Security	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface
PC compatibility 2D compatibility 3D compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D
PC compatibility 2D compatibility 3D compatibility 3D Security	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080)(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@120Hz, 1920x1080@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), 1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese,
PC compatibility 2D compatibility 3D compatibility 3D Security	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@650(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Side (1920x1080@23.98/24Hz), Side by Side(1920x1080@650(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz). HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/jp, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@023.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50/25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humicity 85% Backlit home remote 785BTU/hour 2 10W AC power cord
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@120Hz, 1920x1080@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@50/25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@650(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@120Hz, 1920x1080@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@23.98/24Hz), Side by Side(1920x1080@50/25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@32.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@023.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1920x1080@0120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1920x1080@0120Hz, 1920x1080@0120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1920x1080@0120Hz, 1920x1080@0120Hz
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@32.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@33.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@023.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50/25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humicity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power Supply	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humicity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power Supply Power consumption (standby)	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Side [1920x1080@23.98/24Hz]), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power Power supply Power consumption (standby) Power consumption (min)	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Packing(1280x720@50Hz/60Hz, 1920x1080@120Hz, 1920x1080@120Hz, 1920x1080@120Hz), HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@120Hz), 1920x1080@120Hz), 1920x1080@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@650(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power supply Power consumption (standby) Power consumption (min) Power consumption (min)	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.26/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@120Hz), Side [1920x1080@23.98/24Hz]), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms
PC compatibility 2D compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@510(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms IEEE 802.11 a/b/g/n/ac 2.4GHz/5GHz
PC compatibility 2D compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H)	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920y(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50/25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms IEEE 802.11 a/b/g/n/ac 2.4GHz/5GHz 100V ~ 240V, 50-60Hz < 0.5W 204W 276W 337 x 265 x 119.3
PC compatibility 2D compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages 24/7 operation Operating conditions Remote control Heat dissipation Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - operating frequency Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 1080p(50/60Hz), 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@120Hz, 1920x1080@0120Hz), 1024x768@120Hz, 1280x800@510(25)Hz, 1920x1080@60(30)Hz). Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 785BTU/hour 2 10W AC power cord Remote control Quick start user manual 4.00ms IEEE 802.11 a/b/g/n/ac 2.4GHz/5GHz

