## O HESPERUS™ Series

# Unison™ 240V Switch







#### 1 to 6-Button assembled switch

#### **FEATURES**

- Modern, slim (9.8mm plate depth) glass-look design based on traditional classic shape
- UV stabilised to avoid discolouring
- Switch apertures acceptive of KASTA mechanisms
- Fits standard first fix mounting accessories (e.g. C-clips, nail brackets, wall boxes)
- Flush mounting centres (not recessed) for quicker installation
- Backed off terminal screws and deep tunnels allow fast fitment of cables
- Multiple mounting facilities at both 84mm and 103mm, along with corner fixing points
- Insulated screw caps hinged to the grid plate to provide IP2X rating on mounting screws
- 5 year warranty

#### **ORDERING CODE**


#### H1ASV-WH (number of buttons) (plate finish)

- 1 One switch configuration
- 2 Two switch configuration
- 3 Three switch configuration
- 4 Four switch configuration
- 5 Five switch configuration
- 6 Six switch configuration
- WH White
  - BK Black
  - MT Mint

LOAD

#### **CONNECTION**

#### One Way Switching



### **SPECIFICATIONS**

Power Supply	250V a.c.
Current Rating	10AX
Operating Ambient Temperature	-20 to 40°C
IP Rating	IP20
Plate Depth	9.8mm
Terminal Size	4.1mm bore (accomodates 4x1.5mm² cables)
Terminal Screw Type	Flat Terminal Screw
Mounting Points	84mm / 103mm and Corners
Mounting Screw Type	Combination Flat / Philips Head Screws
Frame Colour / Finish	Black Gloss
Plate Colour / Finish	3 colours (see below) / Transparent
Housing Material	Acrylic / Polycarbonate (PC)
Standards Complied	AS/NZS 3100, AS/NZS 3133

#### **COLOURS**









#### **DIMENSIONS**

