

PRICE LIST



SOURCE • SUPPLY • SUPPORT

ambertech.com.au




	Product Code	Description	UOM	RRP Inc GST
XILICA SOLARO DSP				
	XI-FR1-SOLARO	Fr1-Frame FR1-SOLARO Xilica •Solaro FR1 is a 1U 16-card-slot DSP with modular I/O •Solaro can be populated with any combination of Solaro Series I/O card, offering capabilities including analog audio, USB (with volume/mute HID support), and GPIO	EACH	\$4,199.00
	XI-FR1-SOLARO-D	Solaro FR1-D •Solaro FR1-D is a 1U 16-card-slot DSP with modular I/O •Can be populated with any combination of Solaro Series I/O card, offering capabilities including analog audio, USB (with volume/mute HID support), and GPIO•Solaro FR1-D can handle up-to 64x64 bi-directional channels of audio over Dante, using standard CatX cable with no proprietary switches.	EACH	\$5,949.00
	XI-QR1-SOLARO	Qr1-Frame QR1-SOLARO Xilica Deliver exceptional audio quality to every space with the ultra-small-footprint Solaro QR1, a PoE-powered digital signal processor with eight user-configured I/O card slots. This open-architecture product can be populated with all combinations of Solaro Series I/O modules	EACH	\$2,529.00
	XI-QR1-SOLARO-UC	QR1 SOLARO-UC Open Arch DSP. 8 configurable IO slots. with AEC and USB card .PoE Solaro QR1 UC variant includes all the features of the standard QR 1 with the addition of AEC Hearclear acoustic cancellation license and USB input module XC-SUB.	EACH	\$3,499.00
	XI-SL-AEC	HearClear AEC Software Licence Activation license for FR-1 only. Note. Not available for Solaro QR1	EACH	\$1,199.00
	XI-XC-SGP	Solaro XC-SGP Solaro XC-SGP is a four-channel general-purpose input/output (GPIO) card for Solaro Series processors.The XC-SGP offers the ability to command third-party products and peripherals that are non-networked through both logic or voltage. It is software-selectable for either input or output functionality.	EACH	\$159.00
	XI-XC-SLO	Solaro XC-SLO Solaro XC-SLO is a two-channel analog audio output card for Solaro Series processors. The XC-SLO offers 32-bit D/A conversion and features six-position 3.5mm screw terminals. Solaro XC-SLO ships with mini-Phoenix (female) connectors.	EACH	\$179.00
	XI-XC-SML	Solaro XC-SML Solaro XC-SML is a two-channel analog audio input card for Solaro Series processors.The XC-SML incorporates switchable microphone/line level functionality with optional 48V Phantom power (up-to 75mA with Power-over-Ethernet). It offers 32-bit A/D conversion and features six-position 3.5mm screw terminals. Solaro XC-SML ships with mini-Phoenix (female) connectors.	EACH	\$229.00
	XI-XC-SUB	Solaro XC-SUB •Solaro XC-SUB is a 2x2 (send/receive) USB audio card for Solaro Series processors •Offers volume and mute status sync for Microsoft Teams and connects over a USB 2.0, Type B female connector•Essential for conferencing, education and hybrid applications demanding high quality computer-based audio, leveraging Xilica proprietary signal processing algorithms and HearClear acoustic echo cancellation.	EACH	\$339.00
	XI-XYB-L	XYB-M Xilica and Yamaha Large UC room kit Large UC room kit with QR1, XC-SUB,Sonia Amp , 2 pair of Sonia C5 speakers and Adecia RMCG Ceiling mic	EACH	\$12,394.00
	XI-XYB-M	XYB-L Xilica and Yamaha Medium UC room kit Medium UC room kit with QR1, XC-SUB,Sonia Amp , Sonia C5 speakers(pair) and Adecia RMCG Ceiling mic	EACH	\$11,715.00
XILICA TOUCH CONTROLLERS				
	XI-LUC1	Lucia LUC1 Lucia is a premium IP-based wall remote designed to provide command over audio, video, lighting and building infrastructure in classrooms, multi-purpose spaces and commercial buildings. Lucia offers an OLED display with a single CatX cable for power and data. Lucia is quick and easy to deploy and mounts into a standard Decora single-gang wall box.	EACH	\$1,079.00





	Product Code	Description	UOM	RRP Inc GST
	XI-XTOUCH-TM80	XT80-TTS Table-Top Stand Black,matt for XTOUCH 80 •Premium table-top mounting solution for the XTouch 80 •Easy positioning and installation in corporate conference facilities, classrooms, lecture theaters and courtrooms. • Aluminium stand-mount finished with a durable matt black coating• Incorporating cable access both to the underside and rear for CatX connection• Offers a robust security locking function.	EACH	\$699.00
	XI-XTOUCH80	XTouch 80 •Up-to 16 million colors,a sleek edge-to-edge ultra-slim glass capacitive touch display ideal for conferencing, education and legislative spaces demanding a high-definition, responsive control surface •Simple and quick to install on a table with the optional XT80-TTS stand or on-wall into a standard US dual-gang electrical box, and in both landscape and horizontal orientations.	EACH	\$3,499.00




XILICA I/O INTERFACES

	XI-GIOBT1	Gio Bluetooth Bluetooth 5.0 Class 2 technology, Gio Bluetooth connects personal peripherals such as smartphones, iPads and laptops to an in-room AV system with IT management functionality. Gio Bluetooth installs into a single-gang with just one CatX cable for both power and data, and offers installer-configurable device naming, PIN security and advanced pairing options	EACH	\$1,499.00
--	---------------------------	--	------	------------

XILICA ACCESSORIES

	XI-GIOUSB	GIOUSB Gio USB is a surface-mount USB-to-Dante endpoint, designed to bridge the gap between IT and AV by allowing connection of laptops and room PCs to a networked AV system. Supporting hybrid work and BYOM, Gio USB offers driverless compatibility with leading soft-codec platforms, including two-way volume and mute sync for Microsoft Teams, allowing control of room audio over HID	EACH	\$1,349.00
	XI-GIOXLR	Gio XLR Gio XLR is a dual-gang in-wall endpoint with a single cable installation for both power and data. It offers a 2x2 input/output combination using Neutrik-brand connectors, with mic/line switching and software-selected 48V Phantom power, making Gio XLR a versatile bridge between audio and IT	EACH	\$1,749.00

XILICA SONIA

	XI-SONIA-AMP	SONIA Amplifier Dante enabled,RJ45 mic in . 4 X 15W 4-Ch 4 ohms. PoE++ • PoE++ IP-addressable amplifier designed to power up to eight (8) Sonia C5 5.25" speakers•Four (4) distinct channels that can supply Sonia C5 speakers with either the identical or different audio feeds•Allows a single amplifier to drive audio in anywhere between one and four different rooms• Dante enabled with AES -67 compliance. Microphone: (1) RJ45, PoE power for microphone array	EACH	\$1,189.00
	XI-SONIA-BUNDLE	SONIA BUNDLE Amplifier and C5 speakers(pair) . Bundle For simplicity order the SONIA BUNDLE to receive the Sonia Amplifier and C5 speaker (pair) together.	EACH	\$1,868.00
	XI-SONIA-C5-P	SONIA C5 Speakers (pair) 5.25" in-ceiling . CatX connection .30W 8 ohm 5.25" in-ceiling speaker with Category cable connection, designed to enable anyone to deploy speaker systems into meeting rooms, classrooms and discussion spaces . Plenum-rated, Sonia C5 mounts into suspended ceiling grids using an included tile bracket and double-stepped dog ears, enabling blind installation from below.Sonia C5 features a magnetic, fully-paintable grille with removable logo.	PAIR	\$679.00